



ALNICO HORSESHOES

REFERENCES	Dimensions [mm]				Weight [g]	Grades	Holding force* [kg]
	H	L	I	F			
① 4002013010	7,2±0,05	14,5±0,3	22±0,3	10±0,3	14,5	Alnico 700	1
② 4013013011	13±0,1	12±0,3	26±0,6	10±0,3	22	Alnico 700	1,5
③ 4103022110	17±0,5	24,95±0,5	22±0,5	8±0,3	53	Alnico 600	6
④ 4207012110	29±0,2	17,95±0,15	60±1	24±1	147	Alnico 600	12
⑤ 4215012110	43±1	25,5±1	76±2	45±1,5	315	Alnico 600	21
⑥ 4248012111	38,5±0,1	45±0,5	57±0,5	30±1	417	Alnico 600	27
⑦ 4349092111	42,5±0,5	60±1	89,5±2	54±2	715	Alnico 600	50
⑧ 4344012111	55±0,25	50±1	105±2	65±2	1240	Alnico 600	72
⑨ 4404012110	55±0,1	150±0,5	90±2	40±1	4080	Alnico 600	131
⑩ P410013510	17 +0,1/0	21±0,3	24±0,3	8 +0,15/-0,1	51,3	Alnico 800	4,5

*Indicative average value at room temperature

*This value depends on the nature and surface condition of the substrate