



## RUBBER COATED MAGNET WITH THREADED HOLE

REFERENCES	Dimensions [mm]			Sliding resistance* [kg]	Holding force* [kg]	Weight [g]	Color
	D	H	Drilling				
<b>2402TT5Z</b>	22	6	M4	<b>1,5</b>	<b>3,5</b>	9	Black
<b>2402BT5Z</b>	22	6	M4	<b>1,5</b>	<b>3,5</b>	9	White
<b>2403TT5Z</b>	31	6	M5	<b>1,9</b>	<b>8</b>	21	Black
<b>2403BT5Z</b>	31	6	M5	<b>1,9</b>	<b>9</b>	21	White
<b>2406TT5Z</b>	43	6	M4	<b>3</b>	<b>10</b>	29	Black
<b>2406BT5Z</b>	43	6	M4	<b>3</b>	<b>10</b>	29	White
<b>2407TT5Z</b>	66	8,5	M6	<b>8</b>	<b>25</b>	100	Black
<b>2407BT5Z</b>	66	8,5	M6	<b>8</b>	<b>25</b>	100	White
<b>2408TT5Z</b>	88	8,5	M6	<b>12</b>	<b>55</b>	186	Black
<b>2408BT5Z</b>	88	8,5	M6	<b>12</b>	<b>55</b>	186	White

\*Indicative average value at room temperature



## RUBBER COATED MAGNET + PLASTIC LEVER

REFERENCE	Ø [mm]	H [mm]	Sliding resistance* [kg]	Holding force* [kg]	Weight [g]	Color
<b>2406MT5Z</b>	43	56	<b>3</b>	<b>10</b>	41	Black

\*Indicative average value at room temperature



## MANETTE PLASTIQUE

REFERENCE	H [mm]	Tapping [mm]	Weight [g]	Color
<b>260117000</b>	50	M5	12	Black